

AT 603 - Teknik Özellikler



Description

AT 603 är ett industridäck för lantbruk avsett för arbetsfordon och grävlaster. AT 603 har konstruerats för att säkerställa utmärkt hållbarhet och dragförmåga på drivhjulen och erbjuder maximal prestanda på alla underlag tillsammans med utmärkta självrensande egenskaper. AT 603 i "special"-version har förstärkt däckhölje, medan "HD"-versionen erbjuder förbättrad motståndskraft mot skärande underlag och punktering.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Bekoloder • Uygulamalı makine
Endüstriyel: Bekoloder

Version	STANDARD
Type	TL
Tyre Size	10.5/80 - 18
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8

Dimensions US Standard

Usa code	94019526
Ply Rating	10
Section Width (inch)	10.8
Overall Diameter (inch)	35.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	107.4
Rim Rec	W 9
Rim Alt	W 8 ; 9
ECE	E4-106R-002325

Load capacity (lbs)

mph / psi	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/1/2025 3:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..