

AT 621 - Teknik Özellikler



Description

AT 621, tarımdaki tüm kazma ve yükleme işlemlerinde bekoloderler ve küçük yükleyiciler için uygundur. AT 621 lastiği, mükemmel kesilme ve kopma direnci ve daha yüksek dayanıklılık sağlayan ekstra derin bir sırta sahiptir. Ayrıca, bu BKT lastiği mükemmel dayanıklılık ve kendi kendini temizleme özellikleri sağlar. AT 621, çok farklı kullanıcı gereksinimlerini karşılamak için çeşitli versiyonlarda sunulmaktadır.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Küçük yükleyici • Bekoloder
Endüstriyel: Bekoloder • Yükleyici

Version	STANDARD
Type	TT
Tyre Size	33 X 12.5 - 15

Dimensions US Standard

Usa code	94037209
Ply Rating	8
Section Width (inch)	12.5
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	98.7
Rim Rec	10.00 F SDC
ECE	E11-106R-005230
TRA Code	R4

Load capacity (lbs)

mph / psi	48
5	4700

Printed on 4/27/2024 10:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..