

AT 625 - Teknik Özellikler



Description

AT 625 çiftçilik alanındaki tüm kazı ve yükleme faaliyetlerinde ters kepçe yükleyiciler ve kompakt damperli kamyonlarla kullanım için uygundur. Ekstra derin diş deseni, delinmeye karşı artırılmış dayanıklılık ve sağlamlık sunar. AT 625 kusursuz çekiş ve istikrarın yanı sıra kesilme ve parçalanmalara karşı gelişmiş dayanıklılığa sahiptir.

UM

US Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder • Küçük yükleyici

Version	STANDARD
Type	TT
Tyre Size	14.9 - 24
LI/SS	145 A8

Dimensions US Standard

Usa code	94041367
Ply Rating	12
Section Width (inch)	15.7
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.6
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13 L
TRA Code	R4

Load capacity (lbs)

mph / psi	42
25	6400

Printed on 4/23/2024 10:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..