

AW 09 - Teknik Özellikler



Description

AW 09 uygulamalı makineler, balya makineleri ve römorklar ile toprak işleme, saman hasadı ve taşıma uygulamaları için geliştirilmiştir. Hem yolda hem de yol dışında modern tarım için idealdir. Güçlendirilmiş gövdesi yüksek yük kapasitesi ve daha uzun bir lastik kullanım ömrü sunar. AW 09 olağanüstü anız direnci sağlayan özel bir kesilme ve kopma direncine sahip hamur ile tasarlanmıştır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	110 A8
LI/SS FREE ROLLING	122 A8

Dimensions US Standard

Usa code	94037858
Section Width (inch)	10.6
Overall Diameter (inch)	29.6
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	86.9
Rim Rec	9.00
ECE	E4-106R-000372

Load capacity (lbs)

mph / psi	46
5 FR	4630
15 FR	3940
20 FR	3700
25 FR	3310
5 DW	3270
15 DW	2780
20 DW	2610
25 DW	2340

Printed on 4/25/2024 11:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..