

## AW 09 - Teknik Özellikler



### Description

AW 09 uygulamalı makineler, balya makineleri ve römorklar ile toprak işleme, saman hasadı ve taşıma uygulamaları için geliştirilmiştir. Hem yolda hem de yol dışında modern tarım için idealdir. Güçlendirilmiş gövdesi yüksek yük kapasitesi ve daha uzun bir lastik kullanım ömrü sunar. AW 09 olağanüstü anız direnci sağlayan özel bir kesilme ve kopma direncine sahip hamur ile tasarlanmıştır.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	125 A8
LI/SS FREE ROLLING	138 A8

## Dimensions US Standard

Usa code	94038077
Section Width (inch)	15.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98.1
Rim Rec	13.00
ECE	E4-106R-000379

## Load capacity (lbs)

mph / psi	41
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200
5 DW	5090
15 DW	4330
20 DW	4080
25 DW	3640

Printed on 4/25/2024 8:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..