

AW 09 - Teknik Özellikler



Description

AW 09 uygulamalı makineler, balya makineleri ve römorklar ile toprak işleme, saman hasadı ve taşıma uygulamaları için geliştirilmiştir. Hem yolda hem de yol dışında modern tarım için idealdir. Güçlendirilmiş gövdesi yüksek yük kapasitesi ve daha uzun bir lastik kullanım ömrü sunar. AW 09 olağanüstü anız direnci sağlayan özel bir kesilme ve kopma direncine sahip hamur ile tasarlanmıştır.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	874
Static Loaded Radius (mm)	382
Rolling Circumference (mm)	2561
Rim Rec	AG 13.00
ECE	E4-106R-000381

Load capacity (Kg)

	km/h / bar	3.60
	10 FR	4060
	25 FR	3450
	30 FR	3250
	40 FR	2900
	10 DW	2800
	25 DW	2380
	30 DW	2240
	40 DW	2000

Printed on 4/25/2024 8:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..