

## AW 708 - Teknik Özellikler



### Description

AW 708; uygulamalı makine, römork ve balya makineleri ile toprak işleme, taşıma ve saman hasadı uygulamaları için geliştirilmiştir. Kesilme ve kopmaya karşı dirençli özel hamura sahip HD versiyonu mevcuttur.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork  
Endüstriyel: Römork

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	152 A8

## Dimensions US Standard

Usa code	94047697
Ply Rating	22
Section Width (inch)	18.5
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	99.8
Rim Rec	16.00
ECE	E11-106R-003636

## Load capacity (lbs)

mph / psi	57
5 FR	10960
15 FR	9310
20 FR	8760
25 FR	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/11/2025 3:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..