

AW 708 - Teknik Özellikler



Description

AW 708; uygulamalı makine, römork ve balya makineleri ile toprak işleme, taşıma ve saman hasadı uygulamaları için geliştirilmiştir. Kesilme ve kopmaya karşı dirençli özel hamura sahip HD versiyonu mevcuttur.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork
Endüstriyel: Römork

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

Dimensions US Standard

Usa code	94010356
Ply Rating	18
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00
ECE	E4-106R-001543

Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Printed on 4/24/2024 6:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..