

AW 708 - Teknik Özellikler



Description

AW 708; uygulamalı makine, römork ve balya makineleri ile toprak işleme, taşıma ve saman hasadı uygulamaları için geliştirilmiştir. Kesilme ve kopmaya karşı dirençli özel hamura sahip HD versiyonu mevcuttur.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork
Endüstriyel: Römork

| | |
|--------------------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/50 - 17 |
| LI/SS FREE ROLLING | 152 A8 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94030996 |
| Ply Rating | 16 |
| Section Width (inch) | 19.7 |
| Overall Diameter (inch) | 37.2 |
| Static Loaded Radius (inch) | 16.4 |
| Rolling Circumference (inch) | 108.3 |
| Rim Rec | 16.00 |

Load capacity (lbs)

| mph / psi | 46 |
|-----------|-------|
| 5 FR | 10960 |
| 15 FR | 9310 |
| 20 FR | 8760 |
| 25 FR | 7830 |

Printed on 4/24/2024 6:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..