

AW 711 - Teknik Özellikler



Description

AW 711, modern tarım için özel olarak tasarlanmış ve taşıma, saman hasadı ve toprak işleme uygulamaları için uygun olan radyal bir uygulama lastiğidir. Özel sırt hamuru sayesinde AW 711, ister yumuşak ister sert yüzeylerde kullanılsın, uzun bir kullanım ömrüne sahiptir. Yolda seyahat sırasında düşük yuvarlanma direnci yakıt tüketiminde önemli tasarruf sağlar. VF teknolojisi sayesinde AW 711, düşük şişirme basıncında ağır yükleri taşıyabilir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Saman biçerdöveri • Uygulamalı makine

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	15 R 19.5
LI/SS	139 D

Dimensions US Standard

Usa code	94044931
Section Width (inch)	15.3
Overall Diameter (inch)	40.1
Static Loaded Radius (inch)	18.5
Rolling Circumference (inch)	121.8
Rim Rec	11.75
Rim Alt	12.75
ECE	E11-106R-006649

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73	80
40	1450	1880	2300	2580	3010	3380	3760	4080	4510	5040	5360
30	1850	2400	2950	3290	3850	4320	4800	5210	5760	6450	6850
25	1950	2520	3100	3450	4030	4530	5040	5470	6040	6760	7190
15	2120	2740	3370	3770	4400	4940	5490	5960	6590	7370	7840
5	2940	3810	4680	5220	6090	6850	7610	8280	9150	10230	10880

Printed on 4/19/2024 11:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..