

## AW 711 - Teknik Özellikler



### Description

AW 711, modern tarım için özel olarak tasarlanmış ve taşıma, saman hasadı ve toprak işleme uygulamaları için uygun olan radyal bir uygulama lastiğidir. Özel sırt hamuru sayesinde AW 711, ister yumuşak ister sert yüzeylerde kullanılsın, uzun bir kullanım ömrüne sahiptir. Yolda seyahat sırasında düşük yuvarlanma direnci yakıt tüketiminde önemli tasarruf sağlar. VF teknolojisi sayesinde AW 711, düşük şişirme basıncında ağır yükleri taşıyabilir.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Saman biçerdöveri • Uygulamalı makine

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	340/60 R 16.5
LI/SS	145 A8/B

## Dimensions US Standard

Usa code	94044788
Section Width (inch)	12.8
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.5
Rolling Circumference (inch)	97.5
Rim Rec	11
ECE	E4-106R-001392

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
30	1920	2500	3080	3520	4100	4670	4990	5500	6020	6390
25	1920	2500	3080	3520	4100	4670	4990	5500	6020	6390
20	2150	2800	3440	3950	4590	5240	5590	6160	6730	7160
15	2290	2980	3660	4200	4880	5570	5940	6560	7160	7620
10	2420	3150	3870	4440	5160	5890	6290	6930	7580	8060
5	2690	3490	4300	4930	5730	6540	6990	7700	8420	8950

Printed on 12/10/2023 10:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..