



AW 711 - Veri Sayfasını İndir

Description

AW 711, modern tarım için özel olarak tasarlanmış ve taşıma, saman hasadı ve toprak işleme uygulamaları için uygun olan radyal bir uygulama lastiğidir. Özel sırt hamuru sayesinde AW 711, ister yumuşak ister sert yüzeylerde kullanılsın, uzun bir kullanım ömrüne sahiptir. Yolda seyahat sırasında düşük yuvarlanma direnci yakıt tüketiminde önemli tasarruf sağlar. VF teknolojisi sayesinde AW 711, düşük şişirme basıncında ağır yükleri taşıyabilir.



UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Saman biçerdöveri • Uygulamalı makine

| SIZE | Version | USACode | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|--------------------------------------|-------------------|----------|----------|----------|---------|------|------|------|-------|------|-----------------|
| 265/70 R 16.5 (10 R 16.5) | STUBBLE RESISTANT | 94053292 | 134 A8/B | 8.25 | | 10.4 | 30.4 | 13.5 | 90 | TL | E11-106R-002978 |
| 305/70 R 16.5 (12 R 16.5) | STUBBLE RESISTANT | 94053506 | 148 A8/B | 9.75 | | 12.8 | 33.5 | 14.6 | 100.5 | TL | E11-106R-002995 |
| 340/60 R 16.5 | STUBBLE RESISTANT | 94044788 | 145 A8/B | 11 | | 12.8 | 32.3 | 14.5 | 97.5 | TL | E4-106R-001392 |
| 380/55 R 16.5 | STUBBLE RESISTANT | 94044757 | 150 A8/B | 12 | 11.75 | 14.2 | 32.7 | 14.6 | 98.4 | TL | E4-106R-001393 |
| 395/55 R 16.5 | STUBBLE RESISTANT | 94053469 | 152 A8/B | 12 | | 15.5 | 33 | 14.4 | 99.1 | TL | E11-106R-002997 |
| VF 410/50 R 16.5 | STEEL BELTED | 94055814 | 153 B | AG 11.75 | | 16.1 | 32.9 | 13.8 | 98.9 | TL | E11-106R-005024 |
| VF 480/45 R 17 | STEEL BELTED | 94051434 | 167 A8/B | 16.00 | | 19.3 | 34.1 | 14.3 | 104.1 | TL | E4-106R-002652 |
| 400/60 R 18 | STUBBLE RESISTANT | 94045235 | 159 A8/B | 14 | 13 | 15.5 | 37.2 | 16.5 | 110.5 | TL | E4-106R-001397 |
| 440/55 R 18 | STUBBLE RESISTANT | 94044924 | 159 A8/B | 14 | 13 | 16.1 | 37.2 | 17 | 113.9 | TL | E4-106R-001398 |
| IF 340/65 R 18 | STUBBLE RESISTANT | 94053476 | 153 A8/B | W 11 | | 13 | 35.4 | 15 | 106.4 | TL | E11-106R-002992 |
| 15 R 19.5 | STUBBLE RESISTANT | 94044931 | 139 D | 11.75 | 12.75 | 15.3 | 40.1 | 18.5 | 121.8 | TL | E11-106R-006649 |

Printed on 4/19/2024 5:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..