

AW 726 - Teknik Özellikler



Description

AW 726, taşıma operasyonlarındaki römorklar için özel olarak tasarlanmıştır. Yolda ve yol dışında kullanım için en uygundur. AW 726 mükemmel yol performansı ve kendi kendini temizleme özellikleri sergiler. Blok desen tasarımı, lastik kullanım ömrünü uzatır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Römork

Version	STEEL BELTED
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94067695
Ply Rating	14
Section Width (inch)	11.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	100
Rim Rec	9.00
ECE	E11-106R-006974

Load capacity (lbs)

mph / psi	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 7:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..