

## AW 729 - Teknik Özellikler



### Description

AW 729, taşıma, saman hasadı, balyalama ve toprak işleme uygulamaları için özel olarak tasarlanmış bir tarım lastiğidir. Yuvarlak omuzu ve üç merkezi kanallı sırt tasarımı, düşük toprak sıkıştırması sağlayarak tarlanın zarar görmesini önler.

AW 729, modern çiftçilik için ideal lastiktir ve hem yolda hem de yol dışında kullanıma uygundur.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8

## Dimensions US Standard

Usa code	94065387
Ply Rating	10
Section Width (inch)	15.2
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	100.8
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E11-106R-006434

## Load capacity (lbs)

mph / psi	38
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4680
5 DW	4630
15 DW	3940
20 DW	3700
25 DW	3300

Printed on 4/26/2024 4:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..