

AW 729 - Teknik Özellikler



Description

AW 729, taşıma, saman hasadı, balyalama ve toprak işleme uygulamaları için özel olarak tasarlanmış bir tarım lastiğidir. Yuvarlak omuzu ve üç merkezi kanallı sırt tasarımı, düşük toprak sıkıştırması sağlayarak tarlanın zarar görmesini önler.

AW 729, modern çiftçilik için ideal lastiktir ve hem yolda hem de yol dışında kullanıma uygundur.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	340/55 - 16 (13.0/55 - 16)
LI/SS DRIVE WHEEL	121 A8
LI/SS FREE ROLLING	133 A8

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	785
Static Loaded Radius (mm)	358
Rolling Circumference (mm)	2358
Rim Rec	11.0
ECE	E11-106R-006421

Load capacity (Kg)

	km/h / bar	3.20
	10 FR	2885
	25 FR	2450
	30 FR	2305
	40 FR	2060
	10 DW	2030
	25 DW	1725
	30 DW	1625
	40 DW	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/9/2025 6:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..