

## AW 909 - Teknik Özellikler



### Description

AW 909; uygulamalı makine, römork ve balya makineleri ile toprak işleme, saman hasadı ve taşıma uygulamaları için geliştirilmiştir. Hem yolda hem de yol dışında modern tarım için idealdir.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Balya makinesi • Uygulamalı makine • Römork

Version	STANDARD
Type	TT
Tyre Size	11.5/80 - 15.3
LI/SS FREE ROLLING	141 A8

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	300
<b>Overall Diameter (mm)</b>	844
<b>Static Loaded Radius (mm)</b>	370
<b>Rolling Circumference (mm)</b>	2473
<b>Rim Rec</b>	9.00
<b>ECE</b>	E4-106R-002752

## Load capacity (Kg)

	km/h / bar	5.40
	10 FR	3605
	25 FR	3065
	30 FR	2885
	40 FR	2575

Printed on 4/19/2024 3:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..