

BK 6060 - Teknik Özellikler



Description

BK 6060, hem arazide hem de yolda kullanılabilen, römorklar ve ters kepçe yükleyicilerle taşımacılık için olduğu kadar kazı ve yükleme uygulamalarına da uygun bir lastiktir. Blok desenli lastik, daha uzun bir lastik ömrü sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder • Römork

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	255
Overall Diameter (mm)	925
Static Loaded Radius (mm)	427
Rolling Circumference (mm)	2740
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

Load capacity (Kg)

km/h / bar	7.25
30	2300

Printed on 10/2/2023 8:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..