

## BK 6060 - Teknik Özellikler



### Description

BK 6060, hem arazide hem de yolda kullanılabilen, römorklar ve ters kepçe yükleyicilerle taşımacılık için olduğu kadar kazı ve yükleme uygulamalarına da uygun bir lastiktir. Blok desenli lastik, daha uzun bir lastik ömrü sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Bekoloder • Römork

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16

## Dimensions US Standard

Usa code	94027323
Ply Rating	16
Section Width (inch)	10.4
Overall Diameter (inch)	36.4
Static Loaded Radius (inch)	17
Rolling Circumference (inch)	112.1
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004362

## Load capacity (lbs)

mph / psi	105
20	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 12:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..