

BK 627 - Teknik Özellikler



Description

BK 627 römorklar ve tatbik makineleriyle taşımacılık ve toprak işleme çalışmaları için uygun bir blok desenli lastiktir. Temel olarak araziye yöneliktir ve ağır yük gerektiren işler için idealdir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Traktör • Römork

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	121 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	365
Rolling Circumference (mm)	2495
Rim Rec	6.0
ECE	E11-106R-004256

Load capacity (Kg)

km/h / bar	5.00
40	1450

Printed on 2/24/2024 3:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..