

## BK 823 - Teknik Özellikler



### Description

BK 823, arazide ve yolda çoğunlukla toprak işleme ve taşıma uygulamalarında kullanılan traktörler, uygulamalı makineler ve römorklar için tasarlanmış bir lastiktir. Özel blok deseni, mükemmel direksiyon performansının gerekli olduğu ağır hizmetler için özellikle uygundur. Geliştirilmiş kesilme ve kopmaya karşı dirençli bir HD versiyonu da mevcuttur.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Uygulamalı makine • Traktör • Römork

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	127 A8

## Dimensions US Standard

Usa code	94040131
Ply Rating	14
Section Width (inch)	9.6
Overall Diameter (inch)	35.1
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	101.7
Rim Rec	6.5
ECE	E11-106R-003604

## Load capacity (lbs)

mph / psi	64
25	3860

Printed on 4/25/2024 8:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..