

BK 826 - Teknik Özellikler



Description

Шины BK 826 разработаны специально для эксплуатации на прицепах, используемых для грузовых перевозок. Эта диагональная шина характеризуется повышенной грузоподъемностью благодаря усиленному каркасу. Шины BK 826 также доступны в «индустриальном» исполнении с более высокой устойчивостью к порезам и разрывам, которые подойдут и для экскаваторов-погрузчиков.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Römork

Endüstriyel: Bekoloder • Römork

Version	SPECIAL
Type	TT
Tyre Size	9.00 - 16

Dimensions US Standard

Usa code	94054879
Ply Rating	12
Section Width (inch)	10.4
Overall Diameter (inch)	36.4
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	75
20	4190

Printed on 4/24/2024 4:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..