

BK-LOADER 53 - Teknik Özellikler



Description

BK-LOADER 53, endüstriyel uygulamalarda kullanılan yükleyiciler için tasarlanmış, aramid kuşaklı bir lastiktir. Eşsiz dış lastik yüzü tasarımı, ekstra derin dişleri sayesinde kesilme ve delinmelere ve sırt aşınmasına karşı olağanüstü dayanıklılığın yanı sıra, en iyi yanıl dengeyi sağlar. BK-LOADER 53 sıra dışı kendini temizleme özellikleriyle birlikte hem ıslak hem de kuru yüzeylerde kusursuz tutuşa sahiptir. Bu lastik özellikle geri dönüşüm operasyonları için uygundur.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Yükleyici

Version	ARAMID BELTED
Type	TL
Tyre Size	405/70 R 18
LI/SS	153A2/149A4

Dimensions US Standard

Usa code	94069705
Section Width (inch)	16
Overall Diameter (inch)	41.1
Rim Rec	13
Rim Alt	14 ; 13 SDC; 12 ;12 SDC

Load capacity (lbs)

mph / psi	22	29	36	44	51	58	65	73	80
12	2520	3230	3810	4380	5020	5530	6100	6600	7170
5	2830	3630	4270	4920	5640	6210	6850	7410	8050
STATIC	4520	5810	6850	7880	9030	9940	10970	11880	12900

Printed on 5/9/2024 4:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..