

BOGMAX - Teknik Özellikler



Description

BOGMAX tüm arazi uygulamaları için özel olarak tasarlanmıştır. Çok derin sırt deseni mükemmel çekiş sağlarken, yanak koruyucuları darbeleri ve olası hasarları azaltır. BOGMAX, her durumda spor performansı için mükemmel olan M+S teknolojisine sahip 6 kat dereceli bir lastiktir.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: ATV

Version	STANDARD
Type	TL
Tyre Size	AT 30 X 10 - 14
LI/SS	58 F

Dimensions US Standard

Usa code	94052851
Ply Rating	6
Section Width (inch)	10.2
Overall Diameter (inch)	29.9
Rim Rec	7.0 AT
Rim Alt	7.5 AT ; 8.0 AT

Load capacity (lbs)

mph / psi	7
50	520

Printed on 4/23/2024 6:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..