

COMMANDER (F) - Teknik Özellikler



Description

COMMANDER (F), toprak işleme ve taşıma uygulamaları için mükemmel, önde 3 kuşaklı desenli bir lastiktir. Kesilme ve kopmaya karşı dirençli bir hamurdan yapılmış derin sırtı, yüksek yük kapasitesi ile birlikte daha uzun lastik ömrü sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Tek çeker traktör

Version	STANDARD
Type	TT
Tyre Size	5.50 - 16
LI/SS	86 A6

Dimensions International Standard

Ply Rating	6
TKPH	1
Section Width (mm)	155
Overall Diameter (mm)	720
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2145
Rim Rec	4.00 E
Rim Alt	3.50D ; 4.50E
ECE	E11-106R-003308
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	530

Printed on 4/19/2024 5:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..