

COMMANDER (R) - Teknik Özellikler



Description

ORDER (R), daha uzun lastik kullanım ömrü için güçlü dış tabanlarına sahip derin bir lastik sırtı içeren tarımsal bir lastiktir. Özel çift açılı dış tasarımı, tarlalarda mükemmel çekişe ve kendi kendini temizleme özellikleri sunar. Güçlü gövde, yüksek yük kapasitesi ile daha iyi delinme direnci sağlayan, kesilme ve kopmaya karşı dirençli hamurdan yapılmıştır. COMMANDER (R) toprak işleme, taşıma ve hasat operasyonları için mükemmel bir lastiktir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Biçerdöver • Traktör

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28 (21L)
LI/SS	139 A8

Dimensions US Standard

Usa code	3123123
Ply Rating	12
Section Width (inch)	17.3
Overall Diameter (inch)	56.5
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-009015
TRA Code	R1

Load capacity (lbs)

mph / psi	35
25	5355

Printed on 4/20/2024 4:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..