

## COMMANDER (R) - Teknik Özellikler



### Description

ORDER (R), daha uzun lastik kullanım ömrü için güçlü dış tabanlarına sahip derin bir lastik sırtı içeren tarımsal bir lastiktir. Özel çift açılı diş tasarımı, tarlalarda mükemmel çekişe ve kendi kendini temizleme özellikleri sunar. Güçlü gövde, yüksek yük kapasitesi ile daha iyi delinme direnci sağlayan, kesilme ve kopmaya karşı dirençli hamurdan yapılmıştır. COMMANDER (R) toprak işleme, taşıma ve hasat operasyonları için mükemmel bir lastiktir.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Biçerdöver • Traktör

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 16.9 - 30 |
| LI/SS     | 140 A8    |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94067640        |
| Ply Rating                   | 12              |
| Section Width (inch)         | 17.3            |
| Overall Diameter (inch)      | 58.3            |
| Static Loaded Radius (inch)  | 27.1            |
| Rolling Circumference (inch) | 178.6           |
| Rim Rec                      | W 15 L          |
| Rim Alt                      | W 14 L          |
| ECE                          | E11-106R-006618 |
| TRA Code                     | R1              |

## Load capacity (lbs)

|  |           |      |
|--|-----------|------|
|  | mph / psi | 36   |
|  | 25        | 5510 |

Printed on 4/23/2024 8:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..