

## COMMANDER TWIN RIB - Teknik Özellikler



### Description

COMMANDER TWIN RIB, mükemmel kavrama sağlayan omuz çentikli, 4 kuşaklı desene sahip bir lastiktir. Geniş sırt profili iyi ağırlık dağılımı sağlar. Güçlü gövde, üstün sırt hamuru ile birlikte daha uzun lastik ömrü sağlar. COMMANDER TWIN RIB, toprak işleme ve taşıma uygulamaları için mükemmeldir.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Tek çeker traktör

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 6.50 - 16 |
| LI/SS     | 98 A6     |

## Dimensions International Standard

|                       |                          |
|-----------------------|--------------------------|
| Ply Rating            | 8                        |
| Section Width (mm)    | 180                      |
| Overall Diameter (mm) | 761                      |
| Rim Rec               | 4.50 E                   |
| Rim Alt               | 4.00 E ; 5.00 F ; 5.50 F |
| ECE                   | E11-106R-004107          |
| TRA Code              | F2                       |

## Load capacity (Kg)

| km/h / bar | 4.20 |
|------------|------|
| 30         | 750  |

Printed on 4/19/2024 10:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..