

CON TRAILER - Teknik Özellikler



Description

CON TRAILER özellikle liman uygulamaları için uygun bir römork lastiğidir. Yol ve yol harici uygulamalar için ideal lastiktir. Sağlam yapısı yüksek yük kapasitesi sağlarken, ekstra derin sırt dişleri daha uzun kilometre ömrü sunar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Römork

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	286
Overall Diameter (mm)	1080
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (Kg)

	km/h / bar	9.10	8.40
40 LS		3535	-
40 LD		-	3135

Printed on 4/26/2024 12:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..