

CONTAINER KING - Teknik Özellikler



Description

CONTAINER KING, intermodal taşımacılık ve lojistik uygulamalarında kullanılan konteyner yükleyiciler için tasarlanmıştır. Bu olağanüstü lastik, sırt çatlaklarını en aza indiren, aşınmaya ve yırtılmaya karşı çok dirençli bir sırt hamurundan yapılmıştır. CONTAINER KING, uzun lastik kullanım ömürünün yanı sıra kaldırma modunda olağanüstü sabitleme sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Konteyner yükleyici

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	24
Overall Width (mm)	330
Overall Diameter (mm)	1285
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	10270

Printed on 4/26/2024 4:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..