

## CRANE SPECIAL - Teknik Özellikler



### Description

CRANE SPECIAL engebeli arazilerde kullanılan, kaldırma ve taşıma tipi vinçler için uygundur. Bu lastik, yüksek seviyede istikrar ve dayanıklılık sağlayan özel bir bileşikten üretilmiştir.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Mobil Vinç

Version	STANDARD
Type	TT
Tyre Size	14.00 - 24

## Dimensions US Standard

Usa code	94043934
Ply Rating	24
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	159.4
Rim Rec	10.00 W
TRA Code	E3

## Load capacity (lbs)

mph / psi	83
30	11400

Printed on 4/24/2024 4:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..