

D 405 - Teknik Özellikler



Description

D 405 römorklar ve hafif kamyonlarla taşımacılık uygulamaları için ideal, yola yönelik bir lastiktir. Nizami aşınma ve yol üzerinde kusursuz tutuş, ekstra dayanıklılık sağlar.

UM

International Standard

Construction



Machinery

Zirai: Kamyonet • Römork

Version	STANDARD
Туре	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	14
Section Width (mm)	212
Overall Diameter (mm)	810
Rim Rec	6.00 G
Rim Alt	5.50 F
ECE	E4-54R-0022811

Load capacity (Kg)

km/h / bar	6.90
100 LS	1500
100 LD	1320

Printed on 5/5/2024 6:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..