

DESERT KING - Teknik Özellikler



Description

DESERT KING (Çöl Kralı); gevşek zemin, kumlu arazi ve finişer uygulamaları için çok uygundur. Optimize edilmiş nervürlü sırt tasarımı, mükemmel flotasyon ve yön dengesi sunar. Güçlü naylon gövdesi ve ağır hizmet tipi damağı, düşük basınçlı işlemler için özel olarak geliştirilmiştir. DESERT KING ayrıca yüksek delinme direnci ve daha uzun lastik ömrü sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Çöl Kamyonu

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25 DT

Dimensions International Standard

Ply Rating	16
Section Width (mm)	470
Overall Diameter (mm)	1535
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4405
Rim Rec	10.00/1.5
TRA Code	E7

Load capacity (Kg)

	km/h / bar	2.50
	10	7500
	50	5150
	65	4375

Printed on 4/26/2024 12:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..