

## DON 2000 - Teknik Özellikler



### Description

DON 2000 hem yolda hem de arazide, römorklar ve hafif kamyonlarla yapılan taşımacılık faaliyetleri için uygun bir lastiktir. Tüm ürün ömrü boyunca, yüksek performansı yanı sıra ekstra dayanıklılık sunar.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Kamyonet • Römork

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	216
<b>Overall Diameter (mm)</b>	840
<b>Rim Rec</b>	6.00 G
<b>Rim Alt</b>	5.50 F

## Load capacity (Kg)

	km/h / bar	7.60
	100 LS	1600
	100 LD	1400

Printed on 2/27/2024 3:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..