

DON 2000 - Teknik Özellikler



Description

DON 2000 hem yolda hem de arazide, römorklar ve hafif kamyonlarla yapılan taşımacılık faaliyetleri için uygun bir lastiktir. Tüm ürün ömrü boyunca, yüksek performansı yanı sıra ekstra dayanıklılık sunar.

UM

International Standard

Construction



Machinery

Zirai: Kamyonet • Römork

Version	STANDARD
Туре	π
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	216
Overall Diameter (mm)	840
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (Kg)

km/h / bar	7.60
100 LS	1600
100 LD	1400

Printed on 4/29/2024 2:13 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..