

EARTHMAX CRUSHER HAUL - Teknik Özellikler



Description

EARTHMAX CRUSHER HAUL, hem yolda hem arazideki taşımacılık uygulamaları ve madencilik faaliyetleri için tasarlanmış Tamçelik bir Radyal lastiktir. Güçlü çelik kuşak yapısı ve gövdesi sayesinde, yüksek yük taşıma kapasitesi ile birlikte gelişmiş dayanıklılık ve kilometre performansı sunar. Blok tipi sırt deseni sayesinde mükemmel çekiş sunar. EARTHMAX CRUSHER HAUL olağanüstü sürüş konforuna ek olarak daha az sürüş yorgunluğu ve daha üstün kullanım sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Yol ve yol dışı kamyon

Version	STANDARD
Type	TT
Tyre Size	10.00 R 20
LI/SS	149/146 J

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	272
Overall Diameter (mm)	1065
Rim Rec	7.50
Rim Alt	8.00

Load capacity (Kg)

	km/h / bar	8.30
	100 Load Single	3250
	100 Load Dual	3000

Printed on 4/27/2024 7:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..