

EARTHMAX SR 22 - Teknik Özellikler



Description

EARTHMAX SR 22 (G-2/L-2) Tamamen Çelikten ve şiddetli kış hava şartlarında buz veya kar üzerinde çalışan motorlu greyderler ve yükleyiciler için özel olarak tasarlanmış, radyal bir lastiktir. Araç kullanıcıları, geniş ve doğrusal olmayan diş tasarımının sağladığı kusursuz çekiş ve istikrardan memnun kalırlar.

UM

International Standard

Construction

 RADIAL

Machinery

Endüstriyel: Dozer • Greyder • Yükleyici
Yoldışı: Dozer • Greyder • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/193 A2

Dimensions International Standard

Overall Width (mm)	525
Overall Diameter (mm)	1490
Static Loaded Radius (mm)	640
Rolling Circumference (mm)	4315
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
Star Rating	**
TRA Code	E2/L2

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	5800	6150	6500	6700	6900	7300	-	-	-	-	-
10	-	-	-	-	-	9750	10000	10300	10900	11200	11500

Printed on 4/28/2024 2:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..