

EARTHMAX SR 22 - Teknik Özellikler



Description

EARTHMAX SR 22 (G-2/L-2) Tamamen Çelikten ve şiddetli kış hava şartlarında buz veya kar üzerinde çalışan motorlu greyderler ve yükleyiciler için özel olarak tasarlanmış, radyal bir lastiktir. Araç kullanıcıları, geniş ve doğrusal olmayan diş tasarımının sağladığı kusursuz çekiş ve istikrardan memnun kalırlar.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Dozer • Greyder • Yükleyici
Yoldışı: Dozer • Greyder • Yükleyici

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 161 A8/186 A2 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94040803 |
| Overall Width (inch) | 20.7 |
| Overall Diameter (inch) | 58.7 |
| Static Loaded Radius (inch) | 25.2 |
| Rolling Circumference (inch) | 169.9 |
| Rim Rec | 17.00/2.0 |
| Rim Alt | 17.00/1.7 |
| Star Rating | * |
| TRA Code | G2/L2 |

Load capacity (lbs)

| mph / psi | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 25 | 5360 | 6150 | 6950 | 7600 | 8550 | 9100 | 9650 | 10200 | - | - | - | - | - |
| 5 | - | - | - | - | - | - | - | - | 17600 | 18200 | 19300 | 19800 | 20900 |

Printed on 9/17/2024 3:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..