

## EARTHMAX SR 22 - Teknik Özellikler



### Description

EARTHMAX SR 22 (G-2/L-2) Tamamen Çelikten ve şiddetli kış hava şartlarında buz veya kar üzerinde çalışan motorlu greyderler ve yükleyiciler için özel olarak tasarlanmış, radyal bir lastiktir. Araç kullanıcıları, geniş ve doğrusal olmayan diş tasarımının sağladığı kusursuz çekiş ve istikrardan memnun kalırlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Dozer • Greyder • Yükleyici  
Yoldışı: Dozer • Greyder • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	170 A8/195 A2

## Dimensions US Standard

Usa code	94062911
Overall Width (inch)	24
Overall Diameter (inch)	63.5
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	191.5
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	G2/L2

## Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73
25	6950	7850	8800	9900	10700	11700	12300	13200	-	-	-	-	-
5	-	-	-	-	-	-	-	-	22700	23400	24700	25400	26800

Printed on 4/27/2024 5:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..