

EARTHMAX SR 22 - Teknik Özellikler



Description

EARTHMAX SR 22 (G-2/L-2) Tamamen Çelikten ve şiddetli kış hava şartlarında buz veya kar üzerinde çalışan motorlu greyderler ve yükleyiciler için özel olarak tasarlanmış, radyal bir lastiktir. Araç kullanıcıları, geniş ve doğrusal olmayan diş tasarımının sağladığı kusursuz çekiş ve istikrardan memnun kalırlar.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Dozer • Greyder • Yükleyici
Yoldışı: Dozer • Greyder • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/201 A2

Dimensions US Standard

Usa code	94064342
Overall Width (inch)	24
Overall Diameter (inch)	63.5
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	191.5
Rim Rec	19.50/2.5
Star Rating	**
TRA Code	E2/L2

Load capacity (lbs)

mph / psi	58	62	65	69	73	76	80	83	87	91	94
30	16500	17100	18200	18700	19800	20400	-	-	-	-	-
5	-	-	-	-	-	27600	28300	29100	30000	30900	32000

Printed on 9/17/2024 1:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..