

EARTHMAX SR 23 - Teknik Özellikler



Description

EARTHMAX SR 23 (G-2/L-2) motorlu greyderler ve yükleyiciler için özel olarak tasarlanmış, Tamamen Çelikten, radyal bir lastiktir. İleriye ve yana doğru üstün çekişin yanı sıra, sıra dışı kendini temizleme özelliklerine sahiptir. Dayanıklı gövde ve özellikle kesilmeye karşı dayanıklı diş deseni, uzun bir hizmet ömrü sunar.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Greyder • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	161 A8/186 A2

Dimensions International Standard

Overall Width (mm)	535
Overall Diameter (mm)	1490
Static Loaded Radius (mm)	668
Rolling Circumference (mm)	4489
Rim Rec	17.00/2.0
Star Rating	*
TRA Code	G2/L2

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	2430	2800	3150	3450	3875	4125	4375	4625	--	--	--	--	--
10	--	--	--	--	--	--	--	--	8000	8250	8750	9000	9500

Printed on 4/20/2024 7:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..