

EARTHMAX SR 23 - Veri Sayfasını İndir

Description

EARTHMAX SR 23 (G-2/L-2) motorlu greyderler ve yükleyiciler için özel olarak tasarlanmış, Tamamen Çelikten, radyal bir lastiktir. İleriye ve yana doğru üstün çekişin yanı sıra, sıra dışı kendini temizleme özelliklerine sahiptir. Dayanıklı gövde ve özellikle kesilmeye karşı dayanıklı diş deseni, uzun bir hizmet ömrü sunar.



UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Greyder • Yükleyici

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
15.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	146 A8/169 A2	12.00/1.3		383	1264	559	3756	TL
17.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	153 A8/176 A2	14.00/1.5		448	1345	612	4108	TL
20.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	161 A8/186 A2	17.00/2.0		535	1490	668	4489	TL

Printed on 4/20/2024 10:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..