

EARTHMAX SR 30 - Teknik Özellikler



Description

EARTHMAX SR 30 (E-3/L-3), Tamamen Çelikten ve yükleyiciler ve belden kırma damperli kamyonlar için çift amaçlı, radyal bir lastiktir. Çok katmanlı çelik kuşaklar ve sert blok deseni kusursuz çekiş, istikrar ve dayanıklılık sağlar. Kesilmeye karşı dayanıklı özel bileşik EARTHMAX SR 30'u çeşitli zorlu çalışma koşulu için ideal çözüm haline getirir.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer •
Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B

Dimensions US Standard

Usa code	94054459
TMPH	158
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	E3
Tread Depth	48

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 11:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..