EARTHMAX SR 313 - Teknik Özellikler

Description

EARTHMAX SR 313, sert kayalık koşullarda çalışan Belden Kırmalı Kaya Kamyonları ve Lastikli Yükleyiciler için özel olarak tasarlanmış bir Tamamen Çelik radyal lastiktir. Kesilmeye dayanıklı bileşeni ve özel sırt tasarımı, kesiklere ve hasarlara karşı koruma sağlamasının yanı sıra kendi kendini temizleme özellikleri sunar. Kare omuz tasarımı, mükemmel manevra kabiliyeti için zemin temasını en üst düzeye çıkarır. Çok katmanlı çelik kuşaklarla birlikte Tamamen Çelik radyal yapı ekstra dayanıklılık sağlar. EARTHMAX SR 313, taşıma ve yükleme ve taşıma işlemleri için ideal lastiktir.

UM

International Standard

Construction

RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	160 B/169 A2

Dimensions International Standard

TKPH	135
Overall Width (mm)	394
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3822
Rim Rec	12.00/1.3
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	3650	3875	4000	4250	4375	4500
10	5000	5150	5450	5600	5800	-

Printed on 4/26/2024 7:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..