

EARTHMAX SR 33 PLUS - Teknik Özellikler



Description

EARTHMAX SR 33 PLUS; yumuşak, kumlu, çamurlu ve dolgulu yüzeylerde olağanüstü bir su üzerinde durma kapasitesi ve çekiş sağlamak için özellikle geliştirilen ve tasarlanan Çok Bloklu sırt desenine sahip bir Radyal lastiktir. Güçlü tamçelik gövdesi ve kuşakları, mükemmel dayanıklılık ve çıkıntı ve delinmelere karşı direnç sağlar. EARTHMAX SR 33 PLUS, olağanüstü kendi kendini temizleme kabiliyeti ve üstün denge sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Genel kullanım aracı / Kompaktör

Version	STANDARD
Type	TL
Tyre Size	16.00 R 20
LI/SS	173/170 G

Dimensions US Standard

Usa code	94064038
Overall Width (inch)	17.6
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	156.5
Rim Rec	11.25
Rim Alt	10.00W, 10.0
ECE	E11-54R-0017916

Load capacity (lbs)

mph / psi	110
56	14330

Printed on 4/25/2024 8:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..