

# EARTHMAX SR 33 PLUS - Veri Sayfasını İndir



## Description

EARTHMAX SR 33 PLUS; yumuşak, kumlu, çamurlu ve dolgulu yüzeylerde olağanüstü bir su üzerinde durma kapasitesi ve çekiş sağlamak için özellikle geliştirilen ve tasarlanan Çok Bloklu sırt desenine sahip bir Radyal lastiktir. Güçlü tamçelik gövdesi ve kuşakları, mükemmel dayanıklılık ve çıkıntı ve delinmelere karşı direnç sağlar. EARTHMAX SR 33 PLUS, olağanüstü kendi kendini temizleme kabiliyeti ve üstün denge sunar.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Endüstriyel: Genel kullanım aracı / Kompaktör

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	ECE
16.00 R 20	STANDARD	173/170 G	11.25	10.00W, 10.0	448	1310	582	3974	TL	E11-54R-0017916

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/7/2024 12:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..