

## EARTHMAX SR 33 - Teknik Özellikler



### Description

Earthmax SR 33 çok amaçlı kamyonlar için radyal bir lastiktir. Çok bloklu diş deseni, yumuşak, kumlu veya çamurlu yüzeylerde kusursuz çekişi garanti etmek üzere özel olarak tasarlanmıştır. Earthmax SR 33 en iyi kendini temizleme özelliklerine ek olarak, sürüşte sıra dışı bir istikrar sağlar. Tamamen Çelikten güçlü gövde, kusursuz bir sağlamlığa ve yarıлма ve kesilmeye karşı dayanıklılığa sahiptir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Genel kullanım aracı / Kompaktör

Version	STANDARD
Type	TL
Tyre Size	395/85 R 20
LI/SS	168 J

## Dimensions International Standard

Overall Width (mm)	394
Overall Diameter (mm)	1184
Static Loaded Radius (mm)	538
Rolling Circumference (mm)	3589
Rim Rec	10.00W
Rim Alt	10.00HF
ECE	E11-54R-0017315

## Load capacity (Kg)

km/h / bar	8.50
100	5600

Printed on 4/19/2024 12:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..