

EARTHMAX SR 412 - Teknik Özellikler



Description

EARTHMAX SR 412 (E-4/L-4), yükleme uygulamalarında Belden Kırmalı Kaya Kamyonları, Yükleyiciler ve Dozerler için özel olarak tasarlanmış, Tamamen Çelikten yapılmış bir radyal lastiktir. Güçlü tamçelik gövdesi ve kuşakları, EARTHMAX SR 412'nin mükemmel bir stabiliteyle daha yüksek yükler taşımaya olanak sağlar ve kesiklerin, çıkıntı ve delinmelerden hasar görmesini önler. Benzersiz E-4 sırt deseni sayesinde mükemmel çekiş gücü ve ısıya karşı olağanüstü direnç sağlar. EARTHMAX SR 412, mükemmel manevra kabiliyeti için zemin temasında en üst düzeye çıkan kare bir omuzla geliştirilmiştir.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer • Yükleyici

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 29.5 R 25 |
| LI/SS | 200 B |

Dimensions International Standard

| | |
|----------------------------|-----------|
| TKPH | 252 |
| Overall Width (mm) | 765 |
| Overall Diameter (mm) | 1865 |
| Static Loaded Radius (mm) | 834 |
| Rolling Circumference (mm) | 5543 |
| Rim Rec | 25.00/3.5 |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (Kg)

| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|-------|-------|-------|-------|-------|-------|
| 50 | 11500 | 11800 | 12500 | 12850 | 13600 | 14000 |

Printed on 4/20/2024 5:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..