

## EARTHMAX SR 41 - Teknik Özellikler



### Description

EARTHMAX SR 41 (E-4 / L-4) Belden Kırmalı Kaya Kamyonları, Yükleyiciler ve Dozerler için mükemmel bir Tamçelik radyal lastiktir. Tamamen çelik yapısı ve özel blok diş deseni sayesinde EARTHMAX SR 41, delinmelere karşı mükemmel direnç ve daha uzun kullanım ömrü sağlar. Lastik, kesintisiz uzun çalışma saatlerine ek olarak olağanüstü konfor sunar. EARTHMAX SR 41, yeraltında taşıma işlemlerinde kullanılan Düşük profilli damperli kamyonlar (LPDT) için E4\*\*\*\* olarak da sunulmaktadır.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer • Yükleyici • Düşük profilli damperli kamyon

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

## Dimensions International Standard

TKPH	161
Overall Width (mm)	615
Overall Diameter (mm)	1611
Static Loaded Radius (mm)	725
Rolling Circumference (mm)	4790
Rim Rec	19.50/2.5
Star Rating	**/*
TRA Code	E4/L4

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	7500	7750	8250	8500	9000	9250
10	10300	10600	11200	11500	12150	--

Printed on 4/20/2024 1:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..