

EARTHMAX SR 431 - Teknik Özellikler



Description

EARTHMAX SR 431 (E-4), ağır madencilik koşullarında (yüzey ve yeraltı madenleri) çalışan güçlü taşıma kamyonları için özel olarak tasarlanmış Tamamen Çelik bir lastiktir. Yönsüz sırt deseni mükemmel çekiş ve sabitleme sağlar. Lastik, güçlü bir Tamçelik gövdeye ve kayalık, aşındırıcı ve zorlu ortamlarda bile uzun kullanım ömrünün yanı sıra olağanüstü kesilme ve kopma direnci sağlayan özel bir sırt hamuruna sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	177 B

Dimensions International Standard

TKPH	166
Overall Width (mm)	452
Overall Diameter (mm)	1532
Static Loaded Radius (mm)	713
Rolling Circumference (mm)	4649
Rim Rec	11.25/2.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	5600	5800	6000	6300	6500	6700	6900	7100	7300

Printed on 4/24/2024 3:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..