

## EARTHMAX SR 431 - Teknik Özellikler



### Description

EARTHMAX SR 431 (E-4), ağır madencilik koşullarında (yüzey ve yeraltı madenleri) çalışan güçlü taşıma kamyonları için özel olarak tasarlanmış Tamamen Çelik bir lastiktir. Yönsüz sırt deseni mükemmel çekiş ve sabitleme sağlar. Lastik, güçlü bir Tamçelik gövdeye ve kayalık, aşındırıcı ve zorlu ortamlarda bile uzun kullanım ömrünün yanı sıra olağanüstü kesilme ve kopma direnci sağlayan özel bir sırt hamuruna sahiptir.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Sabit kaya kamyonu

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	177 B

## Dimensions US Standard

Usa code	94062386
TMPH	114
Overall Width (inch)	17.8
Overall Diameter (inch)	60.3
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	183
Rim Rec	11.25/2.0
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	12300	12800	13200	13900	14300	14800	15200	15700	16100

Printed on 4/24/2024 5:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..